

ONGROFOAM

Delivery program:

ONGROFOAM – AHTU; normal density, white

Dimensions:
2020x3050 mm
1560x3050 mm
1220x2440 mm
1000x2000 mm
1220x2440 mm

Thickness:

2 mm 3 mm 4 mm 5 mm 6 mm

2010x3050 mm
1500x3050 mm
1220x2440 mm

1,2 mm

ONGROFOAM – AYTU; ultralight density, white

Dimensions:
2020x3050 mm
1560x3050 mm
1220x2440 mm
1000x2000 mm

Thickness:

2 mm 3 mm 4 mm 5 mm 6 mm

ONGROFOAM – AXTU; ultralight density, white

Dimensions:
2020x3050 mm
1560x3050 mm
1220x2440 mm
1000x2000 mm

Thickness:

8 mm 10 mm

1400x3050 mm

13 mm 15 mm 17 mm 19 mm

ONGROFOAM-AHTN; coloured

Dimensions:
1560x3050 mm

Thickness:

3 mm 5 mm 6 mm

Standard colours:



Other colours are available on request.
Colours are indicative only.

Technical parameters:

Parameters	Unit	Types		
		AHTU/AHTN	AXTU	AYTU
Width	mm	1000-2020		
Tolerance on width	mm	1000-1559 +2,5; -1,0	1560-2020 +3,0; -1,0	
Length	mm	2000 - 3049		
Tolerance on length	mm	2000 - 3049 +5; -1	L ≥ 3050 +6; -1	
Thickness (S)	mm	1,2-6	8-19	2-6
Tolerance on thickness	mm	S±(0,1+0,05S)	S<15mm S±(0,1+0,05S) S>=15mm S±(0,1+0,03S)	S±(0,1+0,05S)
Deviation from the right angle	mm	max. 3mm/1000mm		

Typical applications of ONGROFOAM:



Advertising: signs, exhibition boards, displays, screen printing, digital printing, etc.



Industry: fabrications, control cabinets and boards, etc.



Construction: wall claddings, sandwich panels, interior decorations, etc.

Processing advices:

Fabricating: sawing, drilling, milling

Thermal processing: bending, thermoforming

Others: screen printing, digital printing, vinyl labeling, laminating, painting



www.golemreklama.cz
www.creativefilm.cz

GOLEMREKLAMA

Na Stráži 2392/31b
180 00 Praha 8
tel.: 608 777 028, 777 758 800, 777 758 280
e-mail: obchod@golemreklama.cz



facebook

Najdete nás také na facebooku