

IP 2305 is a special coated polyester fabric. This product has been especially created for digital printing on large-format Inkjets suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

## IP 2305

IP 2305 can be used for advertising banners, textile billboards or posters, textile walls, backgrounds or horizons at trade shows, show rooms, theaters and offices. As the front side of the polyester fabric renders it impermeable, no covering of the reverse side is required during printing. IP 2305 meets the most stringent requirements with respect to material and printing quality. Laminate: ImagePerfect™ water-based liquid laminate with UV protection.

Specifications	
DESCRIPTION	coated polyester fabric
COLOUR	White
THICKNESS	350μ
WEIGHT	320g/m <sup>2</sup>
ADHESIVE	N/A
ADHESIVE STRENGTH	N/A
RELEASE PAPER	N/A
TEMPERATURE RANGE	-20°C to +70°C
DURABILITY (UNPRINTED)	N/A
FLAME RETARDANCY	B1
TOP COAT	PVC
TENSILE STRENGTH	1500 / 900 (N/5cm)      DIN 53354
TEAR RESISTANCE	150 / 80 (N)      DIN 53386
SHELF LIFE	1 year, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© January 2013 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.