

ImagePerfect™ 2306 Plus Canvas Banner is a coated canvas fabric that is fire-rated to B1/M1 levels. It allows with its sophisticated top coat for high levels of printability. This product has been especially created for digital printing on large-format Inkjets suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

IP 2306 Plus

ImagePerfect™ 2306 Plus Canvas Banner is a printable fabric and has the real" look and feel of a canvas. It can be used for large format canvas prints where IP 2320 is not wide enough and for advertising banners, te tile billboards or posters, textile walls, backgrounds or horizons at trade shows, show rooms, theatres and offices. Applications in exhibition environments are facilitated by its high level of B1/M1 fire rating. As the front side of the cotton banner renders it impermeable, no covering of the re erse side is required during printing. Because of its highly sophisticated top-coat, IP 2306 Plus meets the most stringent requirements with respe t to material and printing quality and is highly resistant to creasing and has superb hang-flat properties. Laminate: ImagePerfect™ water-based liquid laminate with UV protection.

Specifications	
DESCRIPTION	100% cotton banner
COLOUR	White
THICKNESS	545μ
WEIGHT	300g/m ²
ADHESIVE	N/A
ADHESIVE STRENGTH	N/A
RELEASE PAPER	N/A
TEMPERATURE RANGE	-30°C to +80°C
DURABILITY (UNPRINTED)	N/A
FLAME RETARDANCY	B1 / M1
TOP COAT	Acrylic
TENSILE STRENGTH	N/A
TEAR RESISTANCE	N/A
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© June 2013 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are infened only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased. Also for horizontal applications, exterior performance will be decreased.

Print-Media have to be properly dried before further processing, like laminating, varnishing or application. The residual solvents can otherwise change the products' specific features.