



SILVER 250 XC

Silver 250 XC films are highly effective at reducing solar heat gain, whilst at the same time continuing to allow some natural light transmission. This film provides effective protection against solar glare, whilst its one-way mirror aspect further guarantees privacy from prying eyes. Its modern design immediately lends a contemporary feel to any building exterior.



SOLAR SCREEN® Warranty
See the notice "new guarantees for the external films"



Fire-resistance rating
M1



Storage from -5°C to +40°C
3 YEARS



European Standard EN 12600
3B3



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **122 cm**

↔ **152 cm**

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	<1 %
Visible light transmission	53 %
Reflection of external visible light	21 %
Reflection of internal visible light	21 %
Total solar energy rejected	56 %
Total solar energy rejected 2*	60 %
Solar ratio :	
Solar energy reflection	30 %
Solar energy absorption	31 %
Solar energy transmission	39 %
Reduction in Solar Glare	47 %
g-value	0.44
u-value	5.8
Emissivity	0.69
Shading coefficient	0.4
Installation type : External application	
Roll length	30,5 m
PET / PVC composition	PET
Thickness	65 µ
Colour : SILVER LIGHT	

INSTALLATION ADVICE

Vertical installation and on standard glass surface**


Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ⚠ Caution ✗ Not recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal shock analysis report.

CONSTRUCTION

- "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
- High optical quality polyester, with anti IR metal particles deposit
- Bonding adhesive
- High optical quality polyester
- PS adhesive, glass polymerization within 15 days
- Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. sun pose 0808 or 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film. The silicone should be applied to the perimeter of the film when it is installed externally, to prevent any oxidation. Please read the notice regarding "new warranty for external films"

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time.