



CLEAR 12 C

Clear12 C films help secure your windows by ensuring that the glass does not shatter, remaining transparent and retaining its overall integrity in the event of an impact, explosion or fire. Ideally suited to covering large glazed expanses, it complies with European Standard EN 12600.



SOLAR SCREEN® Warranty 10 YEARS



Fire-resistance rating **M1**



Storage from -5°C to +40°C



3 YEARS



European Standard EN 12600 1B1



REACH RoHS compliant

RESPECTED





P₂A

WIDTHS AVAILABLE:

122 cm

152 cm

183 cm

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	5 %
Visible light transmission	82 %
Reflection of external visible light	12 %
Reflection of internal visible light	12 %
Total solar energy rejected	20 %
Total solar energy rejected 2*	21 %
Solar ratio:	
Solar energy reflection	10 %
Solar energy absorption	9 %
Solar energy transmission	81 %
Reduction in Solar Glare	16 %
g-value	0.8
u-value	5.7
Shading coefficient	0.9
Installation type: Internal application	
Roll length	30,5 m
Roll length PET / PVC composition	30,5 m PET
_	

INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	V
Tinted single pane	~
Reflective tinted single pane	~
Clear double pane	~
Tinted double pane	~
Reflective tinted double pane	~
Gas-filled double pane - Low E	~
STADIP EXT. clear double pane	~
STADIP INT. clear double pane	~

✓ Yes ! Caution

X Not recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

CONSTRUCTION

- 1. "Hard" scratch resistant layer, for durability and ease of
- maintenance during window cleaning 2. High optical quality polyester 100µ
- 3. Bonding adhesive 4. High optical quality polyester 100µ
- **5.** Bonding adhesive
- 6. High optical quality polyester 100μ
 7. Reinforced PS Adhesive to accompany the elasticity of the film
- in case of impact, glass polymerization within 30 days **8.** Protection release liner, disposable after installation

MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. sun pose 0808 or 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time.