

**LITÉ BLOCKOUT BANNERY**  
**SYMBIO CAST BLOCKOUT BANNER MAT 510G**

**Technický list**

**PVC Blockout technical data sheet**  
**PCZ75133B Matt 510g/m<sup>2</sup> (15 Oz)**

| Item                          |          | Data         | Unit                                     | Ref. test method |
|-------------------------------|----------|--------------|--|------------------|
| <b>Grammage</b>               |          | 510(15)      | g/m <sup>2</sup> (Oz/yard <sup>2</sup> ) | DIN53352         |
| <b>Basic Fabric</b>           |          | 300x300      | Denier                                   |                  |
| <b>Polyester</b>              |          | 42x40        | threads/Inch <sup>2</sup>                |                  |
| <b>Tensile strength</b>       | <b>L</b> | 1300         | N/5cm                                    | DIN53354         |
|                               | <b>W</b> | 1030         | N/5cm                                    |                  |
| <b>Tearing strength</b>       | <b>L</b> | 115          | N/5cm                                    | DIN53356         |
|                               | <b>W</b> | 105          | N/5cm                                    |                  |
| <b>Peeling Strength</b>       |          | 80           | N/5cm                                    | DIN53357         |
| <b>Temperature resistance</b> |          | - 30 to + 70 |  | DIN53372         |
| <b>Width</b>                  |          | 1.067 ~ 3.20 | m  |                  |
| <b>Guarantee</b>              |          | 1 year       |  |                  |

**Remark:** Above technical data on this page is calculated on average, and ± 5% tolerance is acceptable.

For those banners factory can provide warranty for 1 year for outside application.