

## LT 95

## Application Tape

**Description**

Transparent, polyethylene-based mounting film with a fine-pocked finish for the transfer of die-cut and computer-cut letters and symbols.

**Adhesive**

Modified polyacrylate, low adhesive strength.

**Area of use**

This mounting film has been developed for special uses which requires an extraordinary low adhesive power.

**Technical Data**

<b>Thickness*</b> (film with adhesive)	150 micron
<b>Weight*</b> (film with adhesive)	105 g/m <sup>2</sup>
<b>Adhesive power*</b> (FINAT TM 1, after 20 min, stainless steel)	<1 N/25 mm
<b>Tensile strength</b> (DIN EN ISO 527)	along: min. 25 MPa across: min. 25 MPa
<b>Elongation at break</b> (DIN EN ISO 527)	along: min. 500% across: min. 700%
<b>Shelf life**</b>	2 years
<b>Application temperature</b>	> +10°C

\* average

\*\* in original packaging, at 20°C and 50% relative humidity

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.



ORAFOL Europe GmbH – Orafolstraße 2 – D 16515 Oranienburg  
Phone: +49(0)3301/8640 – Fax: +49(0)3301/864100  
Email: [graphic.products@orafol.de](mailto:graphic.products@orafol.de) – Internet: [www.orafol.com](http://www.orafol.com)