

## Product Information

Double-sided mounting tape based on an UV-cross-linked, closed-cell and durable elastic polyethylene foam coated with a solvent acrylic adhesive on both sides.

POLI-MOUNT 3705 offers very good ageing, UV and weathering stability and guarantees a high initial tack on structured and rough surfaces (concrete, structural varnish).

Composite materials with extremely different expansion rates can be mounted without tension.

POLI-MOUNT 3705 is suitable for the following applications:

- Mounting of hooks, holders, consoles, name plates and promotional boards.
- Mounting of mirrors, coverplates, cable trunking and electronic components.
- Self-adhesive mounting of displays and product samples.
- Mounting of objects at exhibitions and shop displays.

## Technical Data

Carrier:	PE-foam, white	
Adhesive:	Solvent acrylic	
Liner:	PE-paper, white (120 g/m <sup>2</sup> )	
Adhesion [N/cm]:	5,80	+/- 10 %
Thickness [mm]:	1,00	+/- 5 %
Temperature resistance [°C]:	-40 / +70	

## Standard Dimensions

1.240 mm x 50 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.