

Product Information

Application Tape based on a one-sided embossed, transparent, dimensionally stable polyethylene film. Ideally suitable for transferring of all cast and calendered PVC CAD/CAM films.

Especially to be emphasised are the following properties:

- The film has a high tensile strength which ensures an exact positioning of all letters. The excellent flatness assists the easy application.
- The acrylic adhesive is specially developed and has a constant high adhesive strength level. It can be removed without residues, even after a long period of application.
- Can be used for dry and wet application.
- Due to the embossed surface, the film unwinds easily. Static charging of the rolls is prevented.

Technical Data

Carrier:	HDPE film, pyramid surface	
Adhesive:	Acrylic, modified	
Adhesion [N/cm]:	1,40	+/- 10 %
Thickness [mm]:	0,13	+/- 5 %

Standard Dimensions

1.220 mm x 100 m

1.000 mm x 100 m

Safety Datasheet

MSDS have not been prepared for these products, they are not subject to the MSDS requirements of the Occupational Safety and Health Administrations Hazard Communication Standard, 29 C.F.R.1910.1200 (b)(6)(v).

When used under reasonable conditions and in accordance with the Poli-Tape directions for use, these products do not present a health and safety hazard.

However, use or processing of the products in a manner which is not in accordance with the directions for use may affect their performance and present potential health and safety hazards.