

OPTIMAL COFR BANNER 450G

Product Information



OPTIMALSELECTION

Coated frontlit banner 450g/m², 1000Dx1000D 18x18

| Item | Data | Test method |
|----------------------|--------------------------------------|---------------------------|
| Fabric | High tenacity yarns 100% PES (1000D) | DIN EN ISO2060 |
| Construction | Weaving 18x18 inch | DIN6001 |
| Total weight | 450 g/sq.m | DIN53352 BS3424 method 5A |
| Weight of fabric | 155 g/sq.m | DIN53352 BS3424 method 5B |
| Weight of PVC | 295 g/sq.m | DIN53352 BS3424 method 5B |
| Tensile strength | Warp: 2300 N/5cm, Weft: 1900 N/5cm | DIN53354 BS3424 method 6A |
| Tearing strength | Warp: 240 N, Weft: 200 N | DIN53356 BS3424 method 7A |
| Adhesion | 80 N/5cm | DIN53357 BS3425 method 9B |
| Suitable temperature | (-20 °C) - (+70 °C) | DIN53372 BS3424 method 10 |

The indexes above are on average, so there will be ±5% tolerance for actual material..

www.golemreklama.cz



www.golemreklama.cz
www.creativefilm.cz

GOLEMREKLAMA

Na Stráži 2392/31b

180 00 Praha 8

tel.: 608 777 028, 777 758 800, 777 758 280

e-mail: obchod@golemreklama.cz



facebook

Najdete nás také na facebooku